Agenda


- Project Status Overview
- Pearl Highlands Facility Flood Assessment
- Waipahu Station Flood Assessment
- Questions and Answers

HONOLULU RAIL THANSIT PROJECT MA

Honolulu Rail Transit Project

Pearl Highlands & Waipahu Transit
Center Hydraulic and Flood
Analysis

Presented to DPP September 23, 2009



Decisions Made


- December 22, 2006
- · City Council selected fixed guideway in exclusive Right-of-Way
- · Known as the Locally Preferred Alternative (LPA)
- Established route, elevated guideway in downtown

Decisions Made

- Transit Mode
 - Fixed guideway in exclusive Right-of-Way
- Alignment
 - Now East Kapolei to Ala Moana Center

• Future - Kapolei to UH Mānoa and Waikīkī Vehicle Technology • Steel wheel on steel rail - "Light Metro" · Widely used, durable, cost-effective







Project Schedule

- Late Summer 2009: Release of Final EIS
- Fall 2009: FTA issues Record of Decision
- · December 2009: Groundbreaking
- Late 2012: Service opens in phases, beginning in Waipahu
- Spring 2019: Start full service

14 (//		
 0.25		


















Model Development • Extent: H-1 -- Kamehameha highway • Geometry: Lidar and new stream surveys • Calibrated: • HWM's from 1991 major flood • HWM's from 2008 bank full flood





































Summary
Design thoroughly considers flood issues
 Compliance with Flood District Regulations Zero Rise within FEMA Floodway
Restores natural floodplain function
 2D model will aid in future design efforts and can be used by City for future activities
nhc Anter recourse specialists




















FLO-2D Model	
Model overview	
2-d model that simulates complex overland flo flooding	ws including urban
Models spatial distribution of depths & velocities	ies
 Accounts for interaction of multiple flow source complex floodplains & in channels 	ces & tlow paths on
→ Unsteady flows (hydrographs)	
Floodplain storage loss & flow obstruction due	e to buildings
→ Approved by FEMA	
A STATE OF THE PARTY OF THE PAR	
nhc	water resource specialists


FLO-2D Model of Waipahu A	rea
Models developed	
Primary area-vride coarse-grid model (50 tt	grid cell size)
Supporting fine-grid model (10 If grid cell s	ize) in vicinity of project stations
Data source	
■ 1 ft contour topography within HHCTCP co	rridor (JCLS 2007)
⇒ 5 tt by 5 tt grid LiDAR data (FEMA 2006)	
→ Building locations & footprints (City of Hor	olulu)
→ USGS 2004 aerial Imagery	
100-year design hydrographs developed by HEC-RAS simulations)	NHC (from hydrologic analysis &
Project features (PB)	
nhc	mater resource specialists









































Summary	
→ 100-year Bood event will cause significance for both with lever & without-lever	
Simulated max munication depths in vic 1-3 ft for with levee A 2-4 ft for without it.	unity of proposed transitistation are up to levia conditions
Simulated max velocities are up to 3.5 flavor conditions	Us for with-levee & 4-0 ft/s for without-
Original station design increases make in up to 0.2-0.5 ft	minitation depities along Farrington Hay by
Project impact is mainly due to obstruct teduction of local conveyance (+ 25%) a restriction of Boodylan sterage	
Impact is mainly caused by maker (sout	h) enfrance huilding localed in flow path
Without makel (south) building or with the detectable impact an flood levels (with the detectable impact an flood levels (with the detectable impact an flood levels).	his building placed on place, project has Ithin model accuracy of 0.1 II)
nhc	mater resource specialists

are corn in any contract a

and the transfer of the same of

and the state of the state of

-- 4 1.00 1550 - 2 pst 1- 2 - 200 /

and the state of the state of the state of the